

HANDRAIL BUTTON STAINLESS STEEL (316)



HANDRAIL BUTTON STAINLESS STEEL

RANGE	Stainless Classic
TYPE	Warning Tactile
MATERIAL	316 marine grade stainless steel
FINISH	Machined
DIMENSIONS	DIA: 10mm THICKNESS: 5mm SHAFT: M6mm x 16mm

FEATURES

Machined, domed button design

Designed for compliance with AS/NZS 1428.1, AS/NZS 1428.4 and with the BCA Section D.

Used when handrails are not continuous and/or no tactile ground surface indicators (TGSI's) are not required. See AS/NZS 1428.4 for further information.

2 year product warranty


APPLICATIONS

Handrails should be designed and installed to comply with AS 1428.1

A minimum clearance of 50mm between the handrail and the adjacent wall or other obstruction should be maintained for the length of the handrail

If further clarification is required please consult AS 1428.1, sections 5, 6, 9 and 10

Disclaimer: No one should act or rely upon the information contained within this document without first referring to the current AS/NZS 1428 Suite of Standards and satisfying themselves that any proposed installations are in accordance with the Australian Standards or with the applicable building regulations, including the Building Code of Australia (BCA), as they apply from one situation to another. Furthermore, the information provided is solely for the purposes of handrail tactile indicators (HRTI's) and is not related to the design, configuration or formation to stairs, handrails, ramps and accessible paths depicted therein.



DTAC PTY LTD
ABN 41 093 070 127

Unit 4, 11-12 Phillip Court
Port Melbourne Victoria
Australia 3207

T 1300 793 478
F 1300 780 628

estimating@dtac.com.au
www.dtac.com.au


PO Box 5059
South Melbourne Victoria
Australia 3205

© DTAC Pty Ltd 2014

INSTALLATION - HANDRAIL BUTTON STAINLESS STEEL (316)

TYPE 1 SUBSTRATES

MASONRY, TIMBER




SOLID (ROUND)

CODE DHB0010

FIXING Drill and glue

NOTE Any thick substrate where maximum anchorage is required




SOLID (SQUARE/RECTANGLE)

CODE DHB0010

FIXING Drill and glue

NOTE Any thick substrate where maximum anchorage is required



SOLID (HERITAGE STYLE)


CODE DHB0010

FIXING Drill and glue

NOTE Any thick substrate where maximum anchorage is required

TYPE 2 SUBSTRATES

METALS




SOLID (ROUND)

CODE DHB0010

FIXING Drill and glue

NOTE Any thick substrate where maximum anchorage is required




SOLID (SQUARE/RECTANGLE)

CODE DHB0010

FIXING Drill and glue

NOTE Any thick substrate where maximum anchorage is required




SOLID (HERITAGE STYLE)

CODE DHB0010

FIXING Drill and glue

NOTE Any thick substrate where maximum anchorage is required

AVAILABLE SIZES



CODE DHB0010