

TACTILE TERRACED BRASS



| | |
|-------------------|--|
| TYPE | Tactile Ground Surface Indicator |
| RANGE | Warning Tactile |
| DESIGN | Terraced |
| MATERIAL | Solid brass |
| FINISH | Machined |
| DIMENSIONS | OUTER DIA: 35mm TOP DIA: 25mm THICKNESS: 5mm |



FEATURES

Machined, concentric circle design on the horizontal face with a terraced slip resistant outer edge

Complies with the NCC (D3.8 Tactile Indicators) and Disability (Access to Premises—Buildings) standards to meet the deemed-to-satisfy-provisions

Complies with slip resistance requirements as detailed in HB 198

Backed by 2 year warranty

Registered design

SLIP RESISTANCE TESTING

Important information: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 198 (HB 198), a Guide to the specification and testing of slip resistance of pedestrian surfaces. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

| | |
|-------------------------|---------------------------------------|
| TEST | AS 4586 APPENDIX A: Wet Pendulum Test |
| FOUR S 96 SLIDER | = 85 CLASS = P5 |
| TRL 55 SLIDER | = 75 CLASS = P5 |

LUMINANCE TESTING

Important information: To determine a luminance contrast between a substrate and the DTAC TGSI, see: AS/NZS 1428.4.1:2009. DTAC can test your substrate for luminance contrast to give you peace of mind that your DTAC project will be fully compliant to AS/NZS 1428.4.1 Appendix E.

| | |
|---|---|
| TEST | AS/NZS 1428.4.1 APPENDIX E PARAGRAPH E3 |
| LUMINANCE REFLECTANCE RATING / WET | = 52.4 |
| LUMINANCE REFLECTANCE RATING / DRY | = 52.3 |

DTAC PTY LTD
ABN 41 093 070 127

Unit 4, 11-12 Phillip Court
Port Melbourne Victoria
Australia 3207

PO Box 5059
South Melbourne Victoria
Australia 3205


T 1300 793 478
F 1300 780 628

estimating@dtac.com.au
www.dtac.com.au

© DTAC Pty Ltd 2020

TACTILE TERRACED INSTALLATION & APPLICATION

SUBSTRATE Stone / Masonry / Timber / Vinyl




CODE DT0310

FIXING Drill and pressure fit
(M8 x 25mm hole)

NOTE Any thick substrate
where maximum hold is
required without chemical
anchoring


SUBSTRATE Vitrified Porcelain / Ceramics / Glass / Metals



CODE DT0310

FIXING Diamond core/pressure fit
(M8 x 25mm hole)

NOTE Any thick substrate
where maximum hold is
required without chemical
anchoring



CODE DT0311

FIXING Direct stick

NOTE Any thick or thin non
drillable substrate