

# TACTILE CLASSIC SILICON CARBIDE STAINLESS STEEL (316)



<b>TYPE</b>	Tactile Ground Surface Indicator
<b>RANGE</b>	Warning Tactile
<b>DESIGN</b>	Classic Silicon Carbide
<b>MATERIAL</b>	316 marine grade stainless steel with silicon carbide infill
<b>FINISH</b>	Machined
<b>DIMENSIONS</b>	<b>OUTER DIA:</b> 35mm <b>TOP DIA:</b> 25mm <b>THICKNESS:</b> 5mm



## FEATURES

Hard wearing, silicon carbide inserted into the horizontal face with a smooth machined outer edge

Complies with the NCC (D3.8 Tactile Indicators) and Disability (Access to Premises—Buildings) standards to meet the deemed-to-satisfy-provisions

Complies with slip resistance requirements as detailed in HB 198

Backed by 2 year warranty

## SLIP RESISTANCE TESTING

Important information: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 198 (HB 198), a Guide to the specification and testing of slip resistance of pedestrian surfaces. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

<b>TEST</b>	AS 4586 APPENDIX A: Wet Pendulum Test
<b>FOUR S 96 SLIDER</b>	= 79 <b>CLASS</b> = P5
<b>TRL 55 SLIDER</b>	= 77 <b>CLASS</b> = P5

## LUMINANCE TESTING

Important information: To determine a luminance contrast between a substrate and the DTAC TGSI, see: AS/NZS 1428.4.1:2009. DTAC can test your substrate for luminance contrast to give you peace of mind that your DTAC project will be fully compliant to AS/NZS 1428.4.1 Appendix E.

<b>TEST</b>	AS/NZS 1428.4.1 APPENDIX E PARAGRAPH E3
<b>LUMINANCE REFLECTANCE RATING / WET</b>	= 4.8
<b>LUMINANCE REFLECTANCE RATING / DRY</b>	= 5.4

DTAC PTY LTD  
ABN 41 093 070 127

Unit 4, 11-12 Phillip Court  
Port Melbourne Victoria  
Australia 3207

PO Box 5059  
South Melbourne Victoria  
Australia 3205


T 1300 793 478  
F 1300 780 628

estimating@dtac.com.au  
www.dtac.com.au

© DTAC Pty Ltd 2020

# TACTILE CLASSIC SILICON CARBIDE INSTALLATION & APPLICATION

**SUBSTRATE** Stone / Masonry / Timber / Vinyl




**CODE** DT0212

**FIXING** Drill and pressure fit  
(M8 x 25mm hole)

**NOTE** Any thick substrate  
where maximum hold is  
required without chemical  
anchoring

**SUBSTRATE** Vitriified Porcelain / Ceramics / Glass / Metals



**CODE** DT0212

**FIXING** Diamond core/pressure fit  
(M8 x 25mm hole)

**NOTE** Any thick substrate  
where maximum hold is  
required without chemical  
anchoring



**CODE** DT0213

**FIXING** Direct stick

**NOTE** Any thick or thin non  
drillable substrate