


TACTILE CLASSIC WHITE URETHANE



TYPE	Tactile
RANGE	Directional Tactile
DESIGN	Classic
MATERIAL	UV stabilised thermo plastic urethane (TPU)
FINISH	Injection moulded



FEATURES

Injection moulded, undulating groove design on the horizontal face with a smooth outer edge

Not intended for use on ramps with an incline greater than 12.5° (1:8)

Designed to comply with AS/NZS 1428.4.1 (Section 3.2 Directional TGSIs)

Complies with the NCC (D3.8 Tactile Indicators) and Disability (Access to Premises—Buildings) standards to meet the deemed-to-satisfy-provisions

Complies with slip resistance requirements as detailed in HB 198

Backed by 2 year warranty

Registered design, Patent pending

SLIP RESISTANCE TESTING

Important information: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 198 (HB 198), a Guide to the specification and testing of slip resistance of pedestrian surfaces. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

TEST AS 4586 APPENDIX A: Wet Pendulum Test

FOUR S 96 SLIDER = 50 **CLASS** = P4

TRL 55 SLIDER = 42 **CLASS** = P4

TEST AS 4586 APPENDIX B: Dry Floor Friction Test

MEAN COF = 0.85 **CLASS** = D1

TEST AS 4586 APPENDIX C: Wet/Barefoot Ramp Test

MEAN ANGLE OF INCLINATION = 20° **CLASS** = B

TEST AS 4586 APPENDIX D: Oil/Wet Ramp Test

CORRECTED MEAN OVERALL ACCEPTANCE ANGLE = 11° **CLASS** = R10

LUMINANCE TESTING

Important information: To determine a luminance contrast between a substrate and the DTAC TGSIs, see: AS/NZS 1428.4.1:2009. DTAC can test your substrate for luminance contrast to give you peace of mind that your DTAC project will be fully compliant to AS/NZS 1428.4.1 Appendix E.

TEST AS/NZS 1428.4.1 APPENDIX E PARAGRAPH E3

LUMINANCE REFLECTANCE RATING / WET = 87.0

LUMINANCE REFLECTANCE RATING / DRY = 86.7

DTAC PTY LTD
ABN 41 093 070 127

Unit 4, 11-12 Phillip Court
Port Melbourne Victoria
Australia 3207

PO Box 5059
South Melbourne Victoria
Australia 3205

T 1300 793 478
F 1300 780 628


estimating@dtac.com.au
www.dtac.com.au

© DTAC Pty Ltd 2020

TACTILE CLASSIC WHITE

INSTALLATION & APPLICATION

SUBSTRATE Stone / Masonry / Timber / Vinyl




CODE DIRP0705W

FIXING Drill and pressure fit

NOTE Any thick substrate where maximum hold is required without chemical anchoring

SUBSTRATE Vitrified Porcelain / Ceramics / Glass / Metals




CODE DIRP0705W

FIXING Diamond core/pressure fit

NOTE Any thick or thin non drillable substrate

SIDE PROFILE



SIZE L290 x W35 x H5mm